

[54] **MATRIX PUSH-BUTTON SWITCH**

[75] Inventors: **Takemi Shimojo; Makoto Yanaga,**
Tokyo, Japan

[73] Assignee: **Alps Electric Co., Ltd.,** Tokyo, Japan

[22] Filed: **Sept. 27, 1971**

[21] Appl. No.: **184,107**

[30] **Foreign Application Priority Data**

Oct. 5, 1970 Japan..... 45/98909

[52] U.S. Cl. **200/166 C, 200/5 A, 200/159 B,**
340/365 R

[51] Int. Cl. **H01h 3/12**

[58] **Field of Search** 200/166 PC, 86 R,
200/5 E, 5 A, 159 B, 168 G, 172 R; 179/90 K;
340/365 R, 365 C

[56] **References Cited**

UNITED STATES PATENTS

3,308,253 3/1967 Krakinowski..... 200/159 B
3,699,294 10/1972 Sudduth..... 200/166 H X

3,676,607 7/1972 Nash et al. 340/365 C X
3,372,246 3/1968 Knuepfer 200/168 G

OTHER PUBLICATIONS

Sedaris et al., Elastic Diaphragm Switch, IBM Technical Disclosure Bulletin 14:3, August 1971, p. 767.

Primary Examiner—Robert K. Schaefer

Assistant Examiner—William J. Smith

Attorney—Maxwell James et al.

[57]

ABSTRACT

A switch has a substrate with a plurality of conductor pairs on it. A resilient cover is disposed over the substrate and has depressible areas aligned with the respective conductor pairs. Conducting contact pieces are mounted on the cover below each of the depressible areas, but normally spaced above the pairs. Upon pressing down a given depressible area, the corresponding contact piece moves to engage the conductor pair associated therewith, and thus closes the circuit between them.

4 Claims, 2 Drawing Figures

